

SPORTDYNO V3.1
DYNAMOMETER: SD325
ROLLER INERTIA: 3.9

DISPLACEMENT COMPENSATION
 COMP. ISO 1585/2535 (temperature and humidity)

TEST NAME	MAX POWER.	MAX TORQUE	TEMP	Humidity %	Pressure	Date/Time
-GX200 STD EXH. STD + CARB ASS.	8.3 / 4357.3	14.6 / 3373.4	32.0 °C	40 %	855.0 mbar	23/06/2005 18:53:29
-HONDA GX 200 STD	6.5 / 4721.0	14.3 / 3045.7	32.0 °C	40 %	855.0 mbar	23/06/2005 15:46:29

DATA FOR TEST: -HONDA GX 200 STD						
RPM	HP (HP)	TQ (N*M)	EXHAUST			
2250	2.6	8.1	1539.3			
2500	3.9	11.1	2335.7			
2750	5.0	12.8	2975.0			
3000	6.1	14.2	3599.4			
3250	6.5	14.0	3842.9			
3450	7.2	14.6	4261.6			
3500	7.2	14.3	4250.5			
3750	7.5	13.9	4422.2			
4000	7.9	13.8	4682.2			
4250	7.7	12.6	4542.6			
4456	8.3	13.1	4931.1			
4500	8.2	12.8	4869.7			
4750	8.0	11.8	4763.8			
5000	7.9	11.0	4689.4			
5250	7.7	10.2	4553.5			
5500	7.3	9.3	4319.4			

